•





Magnification	1x	
Objective Diameter (mm)	50	
Image Intensifier Tube	XD-4, XR5, 4G, 4G+	
Resolution (SOA)	≤80	
Field of View (°)	12°	
Focus Range (m)	10	∞
Brightness adjustment (S/C)	continuous	
Recoil Resistance (g)	500	
Human DRI* 5x zoom (m)	1900/800/350	
Human DRI* 1x zoom (m)	800/370/175	
Power Supply (V)	3 (1xCR123)	
Battery Lifetime** (hrs)	min. 40	
Automatic Shut Down (Y/N/hrs)	Y/3	
Operational Temperature Range (°C)	-40	+60
Storage Temperature Range (°C)	-45	+71
Moisture Resistance [+23/+40°C] (%)	80/98	
Water Resistace (m/hrs)	2/2	
Dimensions*** L x H x W (mm)	196x70x93	
Weight**** (g)	780	

MeoNox DF 1 Tarsius

Night vision clip-on attachment MeoNox DF 1 Tarsius is intended to be used in combination with day time riflescopes for weapons to adopt weapon system to a night conditions or it can be used separately as a night vision monocular for night observation with magnification 1x. The clip-on attachment is placed in front of a riflescope by special adapter by using a quick release (MIL-STD--1913) mount. The device is available with image intensifier tubes IIT of all genereations.

Features

- MeoBright
- MeoDrop
- **Shock Resistant**
- Waterproof
- Nitrogen Purged
- Eternal Bright Control


- (*) Coefficient of atmospheric clarity min. 0,8 at 1 km in natural night illumination 5x10⁻³ lx, when observed target contrast against background is 0,6 for XD-4 IIT


 (**) 1pc Lithium CR 123 3V, 1500 mAh max. intensity brigtness and ambient temperature +20° C

 (****) Without mounts and with covers

 (****) With covers, without mount and batteries

 SOA Second Of Angle





EUROPEAN OPTICS















•















